


- Notes:
- 1.Type:Film to Glass
 - 2.Operating Voltage: ≤10v
 - 3.Operation Temperature: -20 °C ~ 65 °C
Storage Temperature: -30 °C ~ 70 °C
 - 4.Life Time: 1,000,000 times
 - 5.Connect Material: FPC
 - 6.Response Time: ≤10ms
 - 7.Linearity: ≤1.5%
 - 8.Transmittance: ≥75%
 - 9.Surface Hardness ≥3H(pencil)
 - 10.Operation force: 60g ~ 150g
 - 11.Resistance: X: 480Ω-1174Ω Y: 152Ω-371Ω



TOLERANCES
(UNLESS OTHERWISE STATED)
DECIMALS ANGLES ±0.5°

>2000MM	±2.00MM
1800< X ≤2000MM	±1.20MM
1200< X ≤1800MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

格林触控 GreenTouch®		GreenTouch Technology Co.,Ltd			
Model No.:	GT-4W-18.5B-1	Size	18.5"	Ratio	16:9
Structure	G+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015.8.5	Page	1/1
Check	付作书	Date	2015.8.5	Version	A0
Release	汪燕	Date	2015.8.5		