


Notes:

- 1.Type:Film to Film
- 2.Operating Voltage:≤10v
- 3.Operation Temperature:-20℃~65℃
Storage Temperature:-30℃~70℃
- 4.Life Time:1.000.000 times
- 5.Connect Material:FPC
- 6.Response Time:≤10ms
- 7.Linearity:≤1.5%
- 8.Transmittance:≥75%
- 9.Surface Hardness≥3H(pencil)
- 10.Operation force:60g~150g
- 11.Resistance:X:433Ω-1059Ω Y:168Ω-411Ω

Logic:



TOLERANCES (UNLESS OTHERWISE STATED)	
DECIMALS	ANGLES ±0.5°
>200MM	±2.00MM
1600< X ≤2000MM	±1.20MM
1200< X ≤1600MM	±0.80MM
800< X ≤1200MM	±0.50MM
400< X ≤800MM	±0.40MM
120< X ≤400MM	±0.30MM
30< X ≤120MM	±0.20MM
<30MM	±0.10MM

GreenTouch Technology Co.,Ltd		GreenTouch Technology Co.,Ltd			
Model No.:	GT-4W-19B-2	Size	19"	Ratio	16:10
Structure	F+F	Unit	mm	Scale	1:1
Design	李俊	Date	2015.10.5	Page	1/1
Check	付作书	Date	2015.10.5	Version	A0
Release	汪康	Date	2015.10.5		